



DEXTER

Commercial Triple Load T-400 Express Washer

(Model Model
WCAD25KCS-12SZ)



Triple Load T-400 Express Washer

Dexter washers are engineered for the laundry owner demanding greater efficiency, performance and programming capabilities.

Commercial Design

- **Save water** with "sump free" design
- **304 Stainless Steel** keeps Dexter washers looking good
- **Heavy-duty** Sur-Coat Frame is built to last like a battleship
- **Over-sized bearings and seals** run smooth and add to machine life

VFD Technology

- **Reduce installation cost** by using single or three phase power
- **Extend motor life** by ramping current inrush
- **Save electricity** with lower running amperage draw
- **Lower electricity** demand by eliminating spike usage

200 G-Force Extraction

- **Save drying energy** with 200 G-Force extraction
- **Enhance customer turnover** with better washer and dryer performance
- **Achieve consistent results** throughout all washer sizes

Powerful Controls

- **Palm OS®** with built-in infrared port
- **Save programming time** using a handheld computer running optional Palm OS® software
- **Easily customize** pricing, cycles, water temps, supply inputs and more
- **Offer plus cycle**, time of day, and tiered pricing
- **Network capable** with included communication port

Customer Friendly Design

- **Large, easy to use door** for convenient loading and unloading
- **Easy-to-read digital display** including cycle time remaining information
- **Soft touch cycle selection buttons** with temperature icons
- **Ultra-quiet machine operation** improves the laundry environment



Commercial T-400

Express Specifications

Capacity

Load Size	Triple Load	
Dry Weight Capacity	25-30 lbs	11.3-13.6 kg
Cylinder Diameter	25"	63.5 cm
Cylinder Depth	13.375"	33.97 cm
Cylinder Volume	3.8 cu ft	107.6 dm ³

Dimensions

Cabinet Height	48.25"	122.56 cm
Cabinet Width	29.88"	75.90 cm
Overall Depth	28"	71.12 cm
Floor to Door Bottom	16"	40.64 cm
Door Opening	15.25"	38.74 cm

Washing/Extraction

High Extract Speed	200 G-Force	750 RPM
Intermediate Extract Speed	60 G-Force	411 RPM
Washing Speed	50 RPM	
Motor Size	2 HP	1.5 Kw

Electrical

Electrical Phase	Single or Three	
Electrical Voltage (60 Hz)	208-240	
Electrical Running (Amps)	6.2	
Circuit Protection (Amps)	20 amp	
Electrical Wire Size	12 gauge	
Electrical Service (Single Phase)	2 wire + ground	
Electrical Service (Three Phase)	3 wire + ground	

Water

Average Water Usage	25 gal	94.64 L
Maximum Hot Water Usage	11 gal	41.64 L
Water Inlet Size	3/4"	19mm
Water Flow Rate (per minute)	9 gal	34.06 L
Water Pressure (min/max)	30-120 psi	207-827 Kpa
Drain Diameter (O.D.)	3"	7.62 cm
Floor to Center of Drain	5"	12.7

Installation

Net Weight	560 lbs	254 kg
Clearance Between Machines	1/2 (min)	1.27 cm
Clearance Behind Machines	24" (min)	60.96 cm
Concrete Thickness	6" (min)	15.24 cm



DEXTER®

The Dexter Company

2211 W. Grimes, Fairfield, Iowa 52556

www.dexterlaundry.com

1-800-524-2954

© 2006 The Dexter Company

Dexter reserves the right to change features or specifications without notice.



Available with coin drop, programmable electronic drop or Easy Card™.



Easy Programming



Large Loading Door



Emergency Stop Button